MATERIAL SAFETY DATA SHEET

Product Name: Eclipse Floor 200

MSDS ID Number: D-06534 MSDS Date: 06/17/2009

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Eclipse Floor 200

MSDS Number: D-06534
Cancelled MSDS Number: New
MSDS Date: 06/17/2009

Chemical Family Name:See MSDS section II for a list of ingredients. **Product Use:**Concrete Shrinkage reduction Admixture

Chemical Formula: Mixture-NA
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn.
62 Whittemore Avenue
Cambridge, MA 02140
Grace Canada, Inc.
294 Clements Road West
Ajax, Ontario L1S 3C6

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Hexylene glycol	000107-41-5	50-100
Alcohols, C16-18, ethoxylated propoxylated	068002-96-0	1-5

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Caution!

Causes severe eye irritation.
Causes skin irritation.

May be harmful if ingested.

HMIS Rating:

Health: 2
Flammability: 1
Reactivity: 0

Personal Protective Equipment: See section 8

Potential Health Effects:

Inhalation: Acute inhalation not expected to result in adverse effects.

If inhaled as a vapor or mist, causes irritation, sore throat, coughing and breathing difficulty.

Effects include: No other effects expected unless listed below.

Eye Contact: Eye contact can cause severe irritation.

Vapors may cause eye irritation.

Skin Contact: Skin contact causes irritation. Prolonged skin contact can result in burns.

Skin Absorption: Not expected to be harmful if absorbed through the skin.

Ingestion: Harmful if ingested.

Ingestion may cause CNS depression causing dizziness, headache, nausea, uncoordination,

drowsiness and increased reaction time.

SECTION 4 - FIRST AID MEASURES:

Skin Contact: Wash with soap and water.

If discomfort or irritation persists, consult a physician. Remove contaminated clothing and wash before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes while holding eyelids open.

Get immediate medical attention. **Ingestion:** Do not induce vomiting.

Never give anything by mouth to an unconscious person. If discomfort or irritation persists, consult a physician.

MATERIAL SAFETY DATA SHEET

Product Name: Eclipse Floor 200

MSDS ID Number: D-06534 MSDS Date: 06/17/2009

Inhalation: If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200 F

Flash Point Method:

Lower Explosion Limit:

Upper Explosion Limit:

Auto-Ignition Temperature:

Not Applicable

Not Available

Not Available

NFPA Rating:

Health: 2
Flammability: 1
Reactivity: 0

Extinguishing Media: In case of fire, use water spray, dry chemical, Carbon dioxide or foam. **Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

Unusual Fire and Explosion Hazards: When mixed with air and exposed to an ignition source, vapors can burn in open air or explode in confined spaces. Vapors are heavier than air and may travel along ground to ignition sources such as electrical equipment, smoking materials, welding equipment, and pilot lights. Do not cut, drill, grind or weld on or near container whether empty or full. Keep container closed except when in use. Heat from fire can generate flammable vapor. May ignite at temperatures below auto-ignition and normal flash point.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks: Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container. For large spills, dike area and pump waste material into closed containers for disposal or reclamation.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures: Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	Substance Specific and Mineral Dust PELs
Hexylene glycol	-	-	25 ppm	-	-	-	-
			Ceiling	-			-
Alcohols, C16-18, ethoxylated propoxylated	-	-	-	-	-	-	-

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Not generally required.

Personal Protective Equipment:

Respiratory Protection: Respiratory protection is not normally required. However, a chemical cartridge respirator with organic vapor cartridge and a prefilter for dusts/mists is required at or above

MATERIAL SAFETY DATA SHEET

Product Name: Eclipse Floor 200

MSDS ID Number: D-06534 MSDS Date: 06/17/2009

the applicable exposure limits (Consult above Exposure Guidelines). If no limits exist, use an approved respirator whenever a vapor or mist is generated or if respiratory irritation occurs. Supplied air respirator (SCBA) is required at exposure levels above the capabilities of a chemical cartridge respirator.

Skin Protection: Rubber or other impervious gloves should be worn to prevent skin contact. **Eye Protection:** At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygienic Practices: Use good personal hygiene practices.

None beyond those noted above.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Appearance/Odor: Clear Liquid Odor Threshold: (ppm) Not Determined Not Available Vapor Pressure: (Mm Hq) Unknown Vapor Density: (Air = 1) Unknown Solubility In Water: Unknown Specific Gravity: (Water = 1) Not Available **Evaporation Rate:** (Butyl Acetate = 1) Unknown **Boiling Point:** >212°F/100°C Viscosity: Unknown **Bulk Density:** (Pounds/Cubic Foot)(Pcf) Not Applicable % Volatiles (gr/L): (70°F) (21°C) Not Available

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions To Avoid:None known for this product.

Hazardous Polymerization: Will not polymerize.

Hazardous Decomposition Products: None known for this product.

SECTION 11 - TOXICOLOGICAL INFORMATION

Ingredient(No data unless listed.) CAS Number LD50 and LC50

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Hexylene glycol	No	No	No	No	No	No
Alcohols C16-18 ethoxylated propoxylated	No	Nο	No	Nο	Nο	Nο

Mutagenicity:Not applicable.Teratogenicity:Not applicable.Reproductive Toxicity:Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate:No data available for product.

No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name:
UN/NA Number:
Not Applicable
Not Applicable
Nonhazardous
Surface Freight Classification:
Label/Placard Required:
Not Applicable
Not Applicable

MATERIAL SAFETY DATA SHEET

Product Name: Eclipse Floor 200

MSDS ID Number: D-06534 MSDS Date: 06/17/2009

SECTION 15 - REGULATORY INFORMATION

REGULATORY CHEMICAL LISTS:

CERCLA (Comprehensive Response Compensation and Liability Act):

(None present unless listed below)

Chemical Name CAS # Wt % CERCLA RQ

SARA Title III (Superfund Amendments and Reauthorization Act)

SARA Section 312/Tier I & II Hazard Categories:

Health Immediate (acute)

Health Delayed (chronic)

Flammable

Reactive

Pressure

Yes

No

No

No

302 Reportable Ingredients (Identification Threshold 1%.):

Chemical Name CAS # Wt % SARA 302 TPQ

313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):
Chemical Name

CAS # Wt %

National Volatile Organic Compound Emission Standards For Architectural Coatings:

Volatile Organic Content: (gr/L) Not Applicable

WHMIS Classification(s): D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

State Regulatory Information:

<u>California Proposition 65:</u> This product does not contain substances known to the state of California

to cause cancer, birth defects or other reproductive harm.

Massachusetts Hazardous Substance List(Identification threshold 0.0001%(1ppm)):

Chemical Name CAS # Wt %

New Jersey Hazardous Substance List(Identification threshold (0.1%)):

Chemical Name CAS # Wt %

Pennsylvania Hazardous Substance List(Identification threshold 0.01%):

Chemical Name CAS # Wt %

CHEMICAL INVENTORY STATUS:

All chemicals in this product are listed or exempt from listing in the following countries:

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	Yes	No	Yes	Yes	Not Determined	Yes	Yes

SECTION 16 - OTHER INFORMATION

Non-Hazardous Ingredient Disclosure:

Chemical NameCAS NumberWater007732-18-5

Prepared by: EH&S Department Approved by: EH&S Department

Approved Date: 06/17/2009

Disclaimer:

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."